

6/21/2011

80W BAY LIGHT



Actual Product Image May Differ

DATASHEET

PRODUCT CODE: PABL – 018-80

Applications :

Area: Outdoor.

Purpose: Industrial Sheds, Stages, Heritage Buildings, Hoardings & Displays etc.,

Features:

(1) Optical

- » Optical pattern meets all standard Outdoor Light Standards.
- » Uniform illuminance distribution.

(2) Power

- » Switched mode constant current power supply.
- » Over-heat, Over-voltage, Over-current protections are provided.
- » Lightning Protection provided.

(3) Thermal

- » Luminaire surface temperature is 48°C @ $T_a=30^{\circ}\text{C}$, the temperature variation is controlled under 5°C .
- » Junction temperature is controlled at 70°C @ $T_a=30$.

- » Overheat protection will operate to adjust as the LED module surface reaches 80°C.

(4) Luminaire

- » Optimized thermal design to ensure maximum life to LED. The Heat sink grade aluminium has the highest surface area for efficient heat diffusion and the entire luminary with Aluminium acts as heat sink.
- » Dust and water protection design meeting IP65 standards.
- » Super-high luminaire efficacy.

DETAILED TECHNICAL SPECIFICATION

Electrical Characteristics:

PARAMETER	DRIVER RESULT
Input Voltage	160 -260 VAC
Rated Power	80W
Maximum Power	90W
Efficiency	>85%
Power Factor	>0.9
Voltage Harmonics (THD)	<5%
Current Harmonics (THD)	<10%

Operating Conditions:

Operating Frequency	100kHz to 200kHz
Operating Temperature Range	-25°C to +70°C
Storage Temperature Range	-65°C to 125°C
Humidity	95% RH

LED Details:

Led Make	CREE/PHILIPS
No Of LED's	16
Led Viewing Angle	120° by using reflector
Colour Temperature	Cool White (5500 to 6500K)
Luminous Flux	>9500 Lumens
Life Span	> 50,000 Hours
Colour Rendering Index	>70 Ra

LED Luminary Details:

Body	Aluminium Casting Body
Heat Sink	Optimized thermal design to ensure maximum life to LED. The Heat sink grade aluminium has the highest surface area for efficient heat diffusion and the entire luminary with Aluminium acts as heat sink.
Dust and Water protection	IP 65 Standards

Protection Parameters:

Over-Current Protection	Inbuilt
Short-Circuit Protection	Inbuilt
Over-Voltage Protection	Inbuilt
Over-Temperature Protection	135 °C
Lightning Protection	Inbuilt

Gloabtel Convergence Ltd
 190 G, R K Building, Khetwadi Main
 Road, Mumbai 400004
 Tel No: +91 22 40426440
 FAX No: +91 22 66562611
 Email: sales@gloabtel.com/
 rjoshi@gloabtel.com